

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SANIT Lotus Glas- & Keramik Veredelung

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Washing and cleaning products (including solvent based products)

1.3. Details of the supplier of the safety data sheet

Company name:	SANIT-Chemie	
	Reinigungsmittel und -geräte GmbH	
Street:	Dieselstr. 38	
Place:	D-74211 Leingarten	
Telephone:	+49 7131 902100	Telefax: +49 7131 404360
e-mail:	info@sanit-chemie.de	
Contact person:	Produktmanagement	Telephone: 07131 90210-20
Internet:	www.sanit-chemie.de	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 2 of 8

3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			90 - < 95 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
16415-12-6	Silane, hexadecyltrimethoxy-			1 - < 5 %
	240-464-3		01-2119970181-4	
	Skin Irrit. 2; H315			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Material, oxygen-rich, oxidizing. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Washing and cleaning products (including solvent based products)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 4 of 8

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Tested protective gloves are to be worn: Butyl rubber. Thickness of glove material: 0,6mm Breakthrough times and swelling properties of the material must be taken into consideration. penetration time (maximum wearing period): 480 min

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number. Suitable respiratory protective equipment: Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic
pH-Value:	not determined
Changes in the physical state	
Melting point:	-25 °C
Initial boiling point and boiling range:	82 °C
Flash point:	12 °C
Flammability	
Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	425 °C
Auto-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 20 °C)	42 hPa

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 5 of 8

Density (at 20 °C):	0,93 g/cm ³
Water solubility:	easily soluble
Solubility in other solvents	
not determined	
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Vapour density: (at 20 °C)	2,07
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Ignition hazard. In use may form flammable/explosive vapour-air mixture.

10.2. Chemical stability

Materials to avoid: Oxidizing agents, strong.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Oxidizing agents, strong.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	oral	LD50 mg/kg	5050	rat		
	dermal	LD50 mg/kg	12800	rat		
16415-12-6	Silane, hexadecyltrimethoxy-					
	oral	LD50 mg/kg	5002	Rat	OECD 401	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 6 of 8

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

not determined

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h		
	Acute crustacea toxicity	EC50 mg/l	1400	48 h		

12.2. Persistence and degradability

The product has not been tested. not determined

12.3. Bioaccumulative potential

not determined

12.4. Mobility in soil

not determined

12.5. Results of PBT and vPvB assessment

not determined

12.6. Other adverse effects

not determined

Further information

No special environmental measures are necessary.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Waste disposal number of contaminated packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 7 of 8

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

2010/75/EU (VOC): 90 % (837 g/l)
 2004/42/EC (VOC): 90 % (837 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
 Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 1,4,7,8,11,13,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SANIT Lotus Glas- & Keramik Veredelung

Revision date: 19.05.2017

Product code: 3065

Page 8 of 8

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)