

Gewindeflansche PN 10/16 und PN 40
Threaded Flanges PN 10/16 and PN 40
Brides taraudées PN 10/16 et PN 40

Gewindeflansch
DIN 2566 / EN 1092-1 Typ 13
Druckstufe: PN 10/16
Werkstoff: S235 JR

Threaded flange
DIN 2566 / EN 1092-1 Typ 13
pressure level: PN 10/16
material: S235 JR

Bride taraudée
DIN 2566/ EN 1092-1 Type 13
Etage de pression: PN 10/ 16
Matériau: S235 JR



DN	d1	Gewinde	Norm	D	h1	d3	d4	b	k	f	d2	Schrauben	kg
DN	d1	Thread	Norm	D	h1	d3	d4	b	k	f	d2	Screws	kg
DN	d1	Filetage	Norme	D	h1	d3	d4	b	k	f	d2	Vis	kg
15	21,3	R 1/2"	DIN	95	20	35	45	14	65	2	14	4	0,61
20	26,9	R 3/4"	DIN	105	24	45	58	16	75	2	14	4	0,91
25	33,7	R 1"	DIN	115	24	52	68	16	85	2	14	4	1,10
32	42,4	R 1 1/4"	DIN	140	26	60	78	16	100	2	18	4	1,60
40	48,3	R 1 1/2"	DIN	150	26	70	88	16	110	2	18	4	1,78
50	60,3	R 2"	DIN/EN	165	28	84	102	18	125	3	18	4	2,39
65	76,1	R 2 1/2"	DIN	185	32	104	122	18	145	3	18	4	2,97
65	76,1	R 2 1/2"	DIN/EN	185	32	104	122	18	145	3	18	8	2,97
80	88,9	R 3"	DIN/EN	200	34	118	138	20	160	3	18	8	3,78
100	114,3	R 4"	DIN/EN	220	40	140	158	20	180	3	18	8	4,38

schwarz black noire

verzinkt galvanized galvanisé

Gewinde
Thread
Filetage

Norm
Norm
Norme

Best.-Nr.
Art.-No.
No. d'art.

R 1/2"	DIN	62310111
R 3/4"	DIN	62310211
R 1"	DIN	62310311
R 1 1/4"	DIN	62310411
R 1 1/2"	DIN	62310511
R 2"	DIN/EN	62310611
R 2 1/2" (4-Loch)	DIN	62310709
R 2 1/2" (8-Loch)	DIN/EN	62310711
R 3"	DIN/EN	62310811
R 4"	DIN/EN	62310911

Gewinde
Thread
Filetage

Norm
Norm
Norme

Best.-Nr.
Art.-No.
No. d'art.

R 1/2"	DIN	62310122
R 3/4"	DIN	62310222
R 1"	DIN	62310322
R 1 1/4"	DIN	62310422
R 1 1/2"	DIN	62310522
R 2"	DIN/EN	62310622
R 2 1/2" (4-Loch)	DIN	62310720
R 2 1/2" (8-Loch)	DIN/EN	62310722
R 3"	DIN/EN	62310822
R 4"	DIN/EN	62310922

Gewindeflansch
EN 1092-1 Typ 13
Druckstufe: PN 40
Werkstoff: P250 GH, verzinkt

Threaded flange
EN 1092-1 Typ 13
pressure level: PN 40
material: P250 GH, galvanized

Bride taraudée
EN 1092-1 Type 13
Etage de pression: PN 40
Matériau: P250 GH, galvanisé



DN	d1	Gewinde	Norm	D	h1	d3	d4	b	k	f	d2	Schrauben	kg	Best.-Nr.
DN	d1	Thread	Norm	D	h1	d3	d4	b	k	f	d2	Screws	kg	Art.-No.
DN	d1	Filetage	Norme	D	h1	d3	d4	b	k	f	d2	Vis	kg	No. d'art.

15	21,3	R 1/2"	EN	95	22	35	45	16	65	2	14	4	0,72	62340015
20	26,9	R 3/4"	EN	105	26	45	58	18	75	2	14	4	1,04	62340020
25	33,7	R 1"	EN	115	28	52	68	18	85	2	14	4	1,25	62340025
32	42,4	R 1 1/4"	EN	140	30	60	78	18	100	2	18	4	1,81	62340032
40	48,3	R 1 1/2"	EN	150	32	70	88	18	110	3	18	4	2,06	62340040

Edelstahl Gewindeflansch
DIN 2566 / EN 1092-1 Typ 13
Druckstufe: PN 10/16
Werkstoff: 1.4571

Stainless steel threaded flange
DIN 2566 / EN 1092-1 Typ 13
pressure level: PN 10/16
material: 1.4571

Bride taraudée inox
DIN 2566 / EN 1092-1 Type 13
Etage de pression: PN 10/16
Matériau: 1.4571



DN	d1	Gewinde	Norm	D	h1	d3	d4	b	k	f	d2	Schrauben	kg	Best.-Nr.
DN	d1	Thread	Norm	D	h1	d3	d4	b	k	f	d2	Screws	kg	Art.-No.
DN	d1	Filetage	Norme	D	h1	d3	d4	b	k	f	d2	Vis	kg	No. d'art.

15	21,3	R 1/2"	DIN	95	20	35	45	14	65	2	14	4	0,61	61360015
20	26,9	R 3/4"	DIN	105	24	45	58	16	75	2	14	4	0,91	61360020
25	33,7	R 1"	DIN	115	24	52	68	16	85	2	14	4	1,10	61360025
32	42,4	R 1 1/4"	DIN	140	26	60	78	16	100	2	18	4	1,60	61360032
40	48,3	R 1 1/2"	DIN	150	26	70	88	16	110	2	18	4	1,78	61360040
50	60,3	R 2"	DIN/EN	165	28	84	102	18	125	3	18	4	2,39	61360050
65	76,1	R 2 1/2"	DIN/EN	185	32	104	122	18	145	3	18	8	2,97	61360065
80	88,9	R 3"	DIN/EN	200	34	118	138	20	160	3	18	8	3,78	61360080
100	114,3	R 4"	DIN/EN	220	40	140	158	20	180	3	18	8	4,38	61360100