

Three phase hybrid inverters 5 to 12 kW

ASW H-T2 Series



Models (w/ EPS):	Models (w/o EPS):
ASW05kH-T2	ASW05kH-T2-O
ASW06kH-T2	ASW06kH-T2-O
ASW08kH-T2	ASW08kH-T2-O
ASW10kH-T2	ASW10kH-T2-O
ASW12kH-T2	ASW12kH-T2-O



Easy-to-install

- Quick and easy-to-install with standard tools
- Compact wall mount design
- Simple battery and smart meter interfaces for quick and secure installation



Safe & reliable

- Up to 150 % PV array oversizing for higher yields
- Available with or without asymmetrical power output ¹⁾
- UPS level switching time < 10 ms
- IP66 rated design for indoor and outdoor use
- Arc fault circuit interrupter (AFCI) ²⁾



User-friendly

- Smart setup, commissioning and monitoring via Solplanet App
- Intelligent operation modes and smart battery management for DOD / Time of Use / Power setting
- Max. 20 A input current, ideal for bifacial and large PV modules
- Supporting parallel for on-grid and off-grid operation

Technical Datasheet

ASW05kH-T2 ASW06kH-T2 ASW08kH-T2 ASW10kH-T2 ASW12kH-T2

	ASW05kH-T2	ASW06kH-T2	ASW08kH-T2	ASW10kH-T2	ASW12kH-T2						
PV input	Max. PV array power	7500 Wp	9000 Wp	12000 Wp	15000 Wp	18000 Wp					
	Max. input voltage	1100 V									
	MPP voltage range / rated input voltage	150 V to 950 V / 630 V			200 V to 950 V / 630 V ³⁾						
	Min. input voltage / start voltage	60 V / 180 V									
	No. of independent MPPT trackers / strings per MPPT input	2 / 1									
	Max. input current / Max. power per MPP tracker	20 A	7500 W	20 A	9000 W	20 A	10000 W	20 A	10000 W	20 A	10000 W
Max. short-circuit current per MPP tracker	30 A										
Battery input	Battery voltage range	120 V to 600 V									
	Max. charging / discharging power	5000 W	6000 W	8000 W	10000 W	12000 W					
	Max. charging current / Max. discharging current	30 A									
	Battery type	LiFePO4									
AC input	Rated grid voltage	3/N/PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V									
	Rated grid frequency	50 Hz / 60 Hz									
	Max. input power from grid	10000 W	12000 W	16000 W	20000 W	24000 W					
	Max. input current from grid	14.5 A	17.4 A	23.2 A	29.0 A	34.8 A					
AC output	AC voltage range / Nominal AC voltage	270 V to 480 V / 3/N/PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V									
	Rated AC grid frequency	50 Hz / 60 Hz									
	AC grid frequency range	45 ~ 55 Hz / 55 ~ 65 Hz									
	Rated apparent power	5000 VA	6000 VA	8000 VA	10000 VA	12000 VA					
	Max. apparent power	5000 VA	6000 VA	8000 VA	10000 VA	12000 VA					
	Rated grid output current (@400 V)	7.3 A	8.7 A	11.6 A	14.5 A	17.4 A					
	Max. grid output current (@400 V)	8.0 A	9.6 A	12.8 A	16.0 A	19.2 A					
	Power factor at rated power / adjustable range	1 / 0.8 leading to 0.8 lagging									
	Harmonics THDi (@Nominal power)	< 3 % (of nominal power)									
	EPS output	Nominal output voltage	3/N/PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V								
Nominal output frequency		50 Hz / 60 Hz									
Rated apparent power		5000 VA	6000 VA	8000 VA	10000 VA	12000 VA					
Rated current (@400 V)		7.3 A	8.7 A	11.6 A	14.5 A	17.4 A					
Max. current (@400 V, continuous on-grid / off-grid)		14.5 A	7.3 A	17.4 A	8.7 A	23.2 A	11.6 A	29.0 A	14.5 A	34.8 A	17.4 A
Max. power on each phase (@400 V, continuous on-grid / off-grid)		3333 W	1667 W	4000 W	2000 W	5333 W	2667 W	6667 W	3333 W	8000 W	4000 W
Peak output apparent power (@400 V, continuous on-grid / off-grid up to 10s)		10000 VA	10000 VA	12000 VA	12000 VA	16000 VA	16000 VA	20000 VA	20000 VA	24000 VA	24000 VA
Max. switch time		< 10 ms									
Output THDv (@Linear load)		2 %									
Efficiency	MPPT efficiency	99.9 %									
	Euro efficiency / Max. efficiency	97.2 % / 98.0 %	97.5 % / 98.2 %	97.9 % / 98.4 %							
Safety protection	DC surge protection (Type II, according to EN/IEC 61643-11)	●									
	Insulation resistance detection	●									
	PV string input reverse polarity protection	●									
	Battery input reverse polarity protection	●									
	Ground fault monitoring	●									
	Residual current monitoring unit	●									
	AC short circuit protection	●									
	Anti-islanding protection	●									
	Arc fault circuit interrupter (AFCI)	○ ²⁾									
General data	Dimensions (W / H / D)	545 / 465 / 205 mm									
	Weight	24.5 kg									
	Operating temperature range	-25 °C ... +60 °C									
	Cooling concept	Natural convection									
	Noise emission	< 35 dB									
	Degree of protection (as per IEC 60529)	IP66									
	Max. relative humidity	100 %									
	Max. operating altitude	4000 m									
Features	User interface	LED & App									
	BMS interface	CAN									
	Smart meter interface	RS485									
	Communication interfaces	Dongle: WiFi (2.4 GHz) / LAN (100 Mbps) Inverter: RS485 (ModBus RTU), LAN (100 Mbps, Modbus TCP only) ⁴⁾									
	Digital output (dry contact) / No. of outputs	● / 2									
	Digital input (dry contact) / No. of inputs	● / 4									
Integrated power control / export power control	● / ●										

● standard features / ○ optional features / - not available

¹⁾ Asymmetrical power output functionality released in August 2024, please confirm version with Solplanet's sales staff before purchase.

²⁾ AFCI functionality released in April 2025, please confirm version with Solplanet's sales staff before purchase.

³⁾ The latest optimised platform design supports MPP voltage range at 150V-950V, pending subsequent certificate updates.

⁴⁾ Modbus TCP functionality released in April 2025, please confirm version with Solplanet's sales staff before purchase.



Technical Datasheet

ASW05kH-T2-O ASW06kH-T2-O ASW08kH-T2-O ASW10kH-T2-O ASW12kH-T2-O

PV input	Max. PV array power	7500 Wp		9000 Wp		12000 Wp		15000 Wp		18000 Wp	
	Max. input voltage	1100 V									
	MPP voltage range / rated input voltage	150 V to 950 V / 630 V					200 V to 950 V / 630 V ²⁾				
	Min. input voltage / start voltage	60 V / 180 V									
	No. of independent MPPT trackers / strings per MPPT input	2 / 1									
	Max. input current / Max. power per MPP tracker	20 A	7500 W	20 A	9000 W	20 A	10000 W	20 A	10000 W	20 A	10000 W
	Max. short-circuit current per MPP tracker	30 A									
Battery input	Battery voltage range	120 V to 600 V									
	Max. charging / discharging power	5000 W		6000 W		8000 W		10000 W		12000 W	
	Max. charging current / Max. discharging current	30 A									
	Battery type	LiFePO4									
AC input	Rated grid voltage	3/N/PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V									
	Rated grid frequency	50 Hz / 60 Hz									
	Max. input power from grid	5000 W		6000 W		8000 W		10000 W		12000 W	
	Max. input current from grid	7.3 A		8.7 A		11.6 A		14.5 A		17.4 A	
AC output	AC voltage range / Nominal AC voltage	270 V to 480 V / 3/N/PE, 220 V / 380 V; 230 V / 400 V; 240 V / 415 V									
	Rated AC grid frequency	50 Hz / 60 Hz									
	AC grid frequency range	45~55 Hz / 55~65 Hz									
	Rated apparent power	5000 VA		6000 VA		8000 VA		10000 VA		12000 VA	
	Max. apparent power	5000 VA		6000 VA		8000 VA		10000 VA		12000 VA	
	Rated grid output Current current (@400 V)	7.3 A		8.7 A		11.6 A		14.5 A		17.4 A	
	Max. grid output current(@400 V)	8.0 A		9.6 A		12.8 A		16.0 A		19.2 A	
	Harmonics THDi (@ Nominal power)	< 3 % (of nominal power)									
Efficiency	MPPT efficiency	99.9 %									
	Euro efficiency / Max. efficiency	97.2 % / 98.0 %		97.5 % / 98.2 %		97.9 % / 98.4 %					
Safety protection	DC surge protection(Type II, according to EN/IEC 61643-11)	●									
	Insulation resistance detection	●									
	PV string input reverse polarity protection	●									
	Battery input reverse polarity protection	●									
	Ground fault monitoring	●									
	Residual current monitoring unit	●									
	AC short circuit protection	●									
	Anti-islanding protection	●									
General data	Power factor at rated power / adjustable displacement	1 / 0.8 leading to 0.8 lagging									
	Dimensions (W / H / D)	545 mm / 465 mm / 205 mm									
	Weight	24.5 kg									
	Operating temperature range	-25 °C ... +60 °C									
	Cooling concept	Natural convection									
	Noise emission	< 35 dB									
	Degree of protection (as per IEC 60529)	IP66									
	Max. relative humidity	100%									
	Max. operating altitude	4000 m									
Features	User interface	LED & App									
	BMS interface	CAN									
	Smart meter interface	RS485									
	Internet communication interfaces	Wifi / LAN									
	Digital output (dry contact) / No. of outputs	● / 2									
	Digital input (dry contact) / No. of inputs	● / 4									
	Integrated power control / export power control	● / ●									

● standard features ○ optional features - not available

1) Asymmetrical power output functionality released in August 2024, please confirm version with Solplanet's sales staff before purchase.

2) The latest optimised platform design supports MPP voltage range at 150V-950V, pending subsequent certificate updates.

Version: Sep 2024



www.solplanet.net

SOLPLANET INTERNATIONAL
info@solplanet.net
sales@solplanet.net
service.LATAM@solplanet.net
service.EMEA@solplanet.net
service.APAC@solplanet.net



Scan QR code and contact your local team