

Voltage tester SoftFinish® single-pole, 110-250 volts Slotted transparent, with push-on clip 3.0 mm (34745)



Wiha Werkzeuge GmbH
Obertalstraße 3-7
78136 Schonach
E-Mail: info.de@wiha.com
Tel.: +49 (0)7722 959-0

Order no.: 34745

Article number: 34745

EAN: 4010995347451

Customs tariff number: 90303370

Increases your efficiency: Stable and as robust as a fully-fledged screwdriver.

Offers you full protection: Each tool individually tested at 10,000 V AC and approved for 1,000 V AC.

Product dimensions: 140 x 19 x 18 mm (LxWxD)

Application: For determining alternating voltages in low voltage range up to 250 volts with respect to earth potential.

Suitable for trade and industry professionals.

Application: Suitable for trade and industry professionals.

Material: Chrome-vanadium-molybdenum steel, nickel-plated

Tested according to DIN 57680-6, GS, CE compliant.

Customs tariff number	90303370
-----------------------	----------

Slotted 1 (mm)	3.0 mm
----------------	--------

Self service - packing	No
------------------------	----

Cutting strength 1 (mm)	0,50 mm
-------------------------	---------

Handle diameter (mm)	19 mm
----------------------	-------

Visible blade length (mm)	60 mm
---------------------------	-------

Overall length (mm)	140 mm
---------------------	--------

Tool for electrics	No
--------------------	----

Country of origin (ISO 3166-1 Alpha 3)	CHN
--	-----
