



0310272 Professional Work Light Class II – 150W | 21,000 lm | 4000K



IP65

IK08


Class II

Rough service

- **Yellow cable and housing accents for better visibility**
- **Shockproof, heavy-duty construction**
- **High-efficiency output, Class II safety, flicker-free performance**

Engineered for industrial-grade tasks, this 150W LED work light provides exceptionally bright, neutral white light with outstanding energy efficiency. The rugged, impact-resistant housing ensures longevity and durability. With Class II safety certification and flicker-free lighting, it's the ideal solution for large-scale construction sites and heavy-duty professional use.

Image not found or type unknown



General

| | |
|-----------------------|--------------------|
| Type | AC worklight |
| With battery | No |
| Article number | 0310272 |
| Brand | LED'S WORK PREMIUM |
| Warranty time | 5 years |
| Energy label required | Yes |
| Manual required | Yes |
| PLC status | Active |

Lighting

| | |
|-------------------|----------|
| Total lumen | 21000 lm |
| Useful lumen | 17500 lm |
| Luminous efficacy | 140 lm/w |

| | |
|--------------------------------------|---------------|
| Beam angle | 90 ° |
| Light color temperature | 4000 K |
| Light color description | Neutral white |
| Photobiological safety | RG1 |
| Color rendering index | 80 |
| Color consistency in McAdam ellipses | SDCM6 |

Electrical

| | |
|-----------------|-------------|
| Rated power | 150 W |
| Input current | 680 mA |
| Power factor | 0.9 |
| Input voltage | 220-240 VAC |
| Input frequency | 50/60 Hz |
| Dimmable | No |
| Safety class | II |

Performance

| | |
|-------------------------|-------------|
| Lifespan L70B50 | 50000 h |
| Operating temperature | -20 — 45 °C |
| Energy efficiency class | D |
| IP rating | IP65 |
| Impact strength | IK08 |
| Rough service | Yes |

Mechanical

| | |
|------------------|--|
| Article material | Aluminum, Plastic, Polycarbonate (PC) |
| Article height | 454 mm |
| Article depth | 260 mm |
| Article width | 403 mm |
| AC Cable type | H07RN-F 2X1.0 mm ² |
| Cable length | 5 m |
| Cable color | Yellow |
| Plug type | Type C: CEE 7/17 (Contour plug) |
| Article color | Black, Yellow |

Logistic

| | |
|--------------------------------|-------------------------|
| Master carton packing quantity | 2 |
| Master carton packing length | 59 cm |
| Master carton packing width | 45.5 cm |
| Master carton packing height | 47 cm |
| HS code | 9405421000 |
| EAN article | 8721264942043 |
| CBM master carton | 0.126172 m ³ |

View on the website: www.shada.nl/p/0310272