

BALLISTOL CERAMIC DRY LUBRICATION

Product Features

Dry lubrication with lubricating ceramic particles for improved transition from static to sliding friction

Special Features

For long lasting lubrication and sliding activity

Hygienic dry and solid lubrication without oily hands

No adhesion of dirt and dust to the treated surface

No formation of annoying lubricant sludge

Temperature range from -55 °C to +1,000 °C

Application / Practical Tips

Shake well (approx. 20 seconds) and spray from a distance of 10-25 cm. Dry and ready for use after a short time.

In sensitive areas, e.g. when handling textiles or paper or when there is a high level of dust

To reduce friction in casters and bearings, slide and guide rails, cables and telescope mechanisms, transmissions and gearwheels, as well as all kinds of plastics

For lubricating oven racks (e.g. baking ovens)



Available as

200 ml

400 ml

5 litre

art.no.

26630

25640

25650

Physical and Chemical Characteristics

Appearance: colourless, clear

Odour: alcohol-like

pH value: approx. 7.5 (at 20 °C)

Flash Point: approx. -104 °C (propane)

Boiling Point: approx. 78 °C

Vapour pressure: approx. 60 hPa (at 20 °C, regarding liquid phase)

Relative density: approx. 0.82 g/cm³ (at 20 °C, regarding liquid phase)

Solubility: freely miscible

Lower Explosion Limit: 1.5 vol-% (propane)

Upper Explosion Limit: 10.9 vol-% (propane)

Temperature Application Range: -40 °C to approx. +250 °C

Hazard Statement

Extremely flammable aerosol.

Causes serious eye irritation.

Pressurised container: May burst if heated.

Important Product Advantages

- Finest ceramic particles for permanent lubrication
- Without oil or grease
- Hygienic, clean and nature-friendly product
- Long lasting lubrication and sliding activity
- Optimizes the transition from static to sliding friction
- High material compatibility (all metal and plastic parts)
- Does not resinify
- Free from silicone and acids



Other products among BALLISTOL's technical products

Premium Rust Protection Oil

Multifunctional Garage Oil

Multi-Purpose Grease

Silicone Oil

Fine Mechanical Oil



BALLISTOL GmbH
Ballistolweg 1
D-84168 Aham
Tel. +49 (0) 8744 9699-0
Fax +49 (0) 8744 9699-99
info@ballistol.de
www.ballistol.de/shop/en