


Girella con dado in ottone o acciaio inox e guarnizione piatta in EPDM

Adaptor with union nut in brass/stainless steel and EPDM flat seal

Anschlussverschraubung mit EPDM-Flachdichtung und Messing-oder Inoxmutter




Code	d - G (ISO 228)	Dado Nut Überwurf.	L	Z	g	MOQ
S60PC-LBP	15-G $\frac{1}{2}$		52	22	65	50
S60QC-LBP	15-G $\frac{3}{4}$		50	22	90	50
S60SC-LBP	15-G1 $\frac{1}{4}$		51	20	190	15
S60QD-LBP	18-G $\frac{3}{4}$	Ottone	36	8	66	50
S60RE-LBP	22-G1	Brass	39	7	106	50
S60RF-LBP	28-G1	Messing	60	26	159	50
S60SF-LBP	28-G1 $\frac{1}{4}$		44	10	168	50
S60TF-LBP	28-G1 $\frac{1}{2}$		73	38	170	50
S60TG-LBP	35-G1 $\frac{1}{2}$		48	11	260	20
S60UH-LBP	42-G1 $\frac{3}{4}$		53	9	292	20
S60VH-LBP	42-G2		57	11	509	20
S60WJ-LBP	54-G2 $\frac{5}{8}$		61	10	454	20
S61QC-LBP	15-G $\frac{3}{4}$		51	22	100	50
S61SC-LBP	15-G1 $\frac{1}{4}$		52	20	90	15
S61QD-LBP	18-G $\frac{3}{4}$		38	8	70	50
S61RE-LBP	22-G1	Inox	39	7	115	50
S61SF-LBP	28-G1 $\frac{1}{4}$	Stainless steel	44	10	165	50
S61TF-LBP	28-G1 $\frac{1}{2}$	Edelstahl	73	38	308	50
S61TG-LBP	35-G1 $\frac{1}{2}$		48	11	275	20
S61UH-LBP	42-G1 $\frac{3}{4}$		53	9	285	20
S61WJ-LBP	54-G2 $\frac{5}{8}$		61	10	420	20

Girella con dado in ottone o acciaio inox e raccordo femmina e guarnizione piatta in EPDM

Adaptor union with female thread, brass/stainless steel nut and EPDM flat seal

Übergangverschraubung I.G. mit EPDM-Flachdichtung und Messing- oder Inoxmutter



Code	d - Rp	Dado Nut Überwurf.	L	Z	g	MOQ
S62PC-LBP	15-Rp $\frac{1}{2}$		73	41	150	15
S62QC-LBP	15-Rp $\frac{3}{4}$		76	43	205	15
S62PD-LBP	18-Rp $\frac{1}{2}$		59	27	132	15
S62QD-LBP	18-Rp $\frac{3}{4}$	Ottone	62	29	190	15
S62QE-LBP	22-Rp $\frac{3}{4}$	Brass	63	28	220	15
S62RE-LBP	22-Rp1	Messing	67	30	270	15
S62RF-LBP	28-Rp1		71	33	420	15
S62SG-LBP	35-Rp1 $\frac{1}{4}$		77	34	520	15
S62TH-LBP	42-Rp1 $\frac{1}{2}$		82	33	590	15
S62VJ-LBP	54-Rp2		95	37	1080	15
S63PC-LBP	15-Rp $\frac{1}{2}$		73	41	160	15
S63QC-LBP	15-Rp $\frac{3}{4}$		76	43	220	15
S63PD-LBP	18-Rp $\frac{1}{2}$		59	27	150	15
S63QD-LBP	18-Rp $\frac{3}{4}$	Inox	62	29	205	15
S63QE-LBP	22-Rp $\frac{3}{4}$	Stainless steel	63	28	230	15
S63RE-LBP	22-Rp1	Edelstahl	67	30	280	15
S63RF-LBP	28-Rp1		71	33	400	15
S63SG-LBP	35-Rp1 $\frac{1}{4}$		77	34	462	15
S63TH-LBP	42-Rp1 $\frac{1}{2}$		82	33	484	15
S63VJ-LBP	54-Rp2		95	37	1035	15