







Product Name: Lithium Battery

中国认可 国际互认 INSPECTION **CNAS IB0551**  Page 1 of 15 Pages

Report No.: HZHY20160721SDS01

## SAFETY DATA SHEET

Type/ Model: 16340 3.7V 550mAh	
Revision Date: July. 25, 2016	

Compiler: Gao Pu zheng

Reviewer: Mr Parsfei

Approver: Liangungcherg



Guangzhou MCM Certification and Testing Co., Ltd.









Report No.: HZHY20160721SDS01 Page 2 of 15 Pages

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product Identifier**

Name of Product: Lithium Battery

#### 1.2 Other means of identification

Product Models: 16340 Nominal Voltage: 3.7V Nominal capacity: 550mAh Nominal Power: 2.04Wh

Weight: 18g

#### 1.3 Recommended use of the chemical and restriction on use

Recommended Use: Rechargeable Li-ion Battery Restriction on Use: No information available

#### 1.4 Information Of Supplier:

**Company Name:** Huizhou HeYing Electronics Technology Co., LTD **Address:** Yudi Industrial Zone, ChenJiangTown, Huizhou City, GuangDong

**Zip code:** 516029

Contact person: Lei Chuan

**Tel:** 18819661512

E-mail: LeichuaN@foxmial.com

#### 1.5 Emergency Telephone

18819661512

### **SECTION 2. Hazard(s) Identification**

#### 2.1 Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an SDS per the OSHA hazard communication standards unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity – Oral	Category 4
Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category C
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

#### 2.2 Label elements

#### 2.2.1 Signal Word Danger

#### 2.2.2 Hazard Statements

Harmful if swallowed Toxic if swallowed Harmful in contact with skin Cause severe skin burns and eye damage May cause an allergic or reaction May cause cancer Report No.: HZHY20160721SDS01 Page 3 of 15 Pages

Cause damage to organs
May cause respiratory irritation

#### 2.2.3 Symbol







This product is an article which contains a chemical substance. Safety information is given for exposure to the article as solid. Intended use of the product should not result in exposure to the chemical substance, This is a battery. In case of rupture: the above hazards exist.

#### 2.3 Precautionary Statements

#### 2.3.1 Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Keep away from flames and hot surface –no smoking.

Do not breath dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Wear protective gloves

#### 2.3 .2Precautionary Statements – Response

If exposed or connected: Get medical advice/attention. Specific treatment(see supplemental first aid/instruction on this label).

#### Skin

If on skin: wash with plenty of soap and water. Take off contaminated clothing and water before reuse, if skin irritation or rash occurs: get medical advice/attention if feel unwell.

#### Eye

If in eyes: Rinse cautiously with water for several minutes, remove contact lenses, if present and easy to do, Continue rinsing. Call a poison center or doctor/physician.

#### **Inhalation**

If inhalation: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

#### Ingestion

If swallowed: rinse mouth, do not induce vomiting ,Call a poison center or doctor/physician if feel unwell.

#### 2.3.3 Precautionary Statements - Storage

Store locked up

#### 2.3.4 Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

#### 2.4 Hazards not otherwise classified (HNOC)

Not applicable

Report No.: HZHY20160721SDS01 Page 4 of 15 Pages

#### 2.5 Unknown Toxicity

10% of the mixture consists of ingredient(s) of unknown toxicity.

#### 2.6 Other information

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.7 Interactions with other chemicals

Use of alcoholic beverages may enhance toxic effect.

### **SECTION 3. Composition/Information on Ingredients**

Chemical Name	Molecular formula	CAS No.	Weigh%
Nickel Cobalt Lithium Manganate	LiNixCoyMnzO <sub>2</sub>	182442-95-1	44.29
Graphite	C <sub>24</sub> X <sub>12</sub>	7782-42-5	19.71
N-methyl pyrrolidone	C₅H <sub>9</sub> NO	872-50-4	16.50
Copper Foils	Cu	7440-50-8	7.30
Aluminum Foils	Al	7429-90-5	12
Nickel	Ni	7440-02-0	0.20

### 4. First Aid Measures

#### 4.1 General Advice

First aid is Applicable only in the case of cell rupture.

#### 4.1.1 Eye contact

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eyes wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area.

#### 4.1.2 Skin Contact

Wash off immediately with plenty of water and soap for at least 15 minutes. In the case of skin irritation or allergic reaction see a physician. May cause an allergic skin reaction.

#### 4.1.3 Inhalation of Vented Gas

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substances; give artificial respiration with the aid of a pocket mask equipped with a one-way value or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.

#### 4.1.4 Ingestion

Do not induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

#### 4.1.5 Self-protection of the first aider

Report No.: HZHY20160721SDS01 Page 5 of 15 Pages

Ensure that medical personnel are aware of the material(s) involved. Take precaution to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personnel protective equipment as required. Wear personnel protective clothing (see section8).

#### 4.2 Most important symptoms and effects, both acute and delayed

Burning sensation, Itching. Rashes. Hives, Coughing.

#### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to physician

Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization of susceptible persons. Treat symptomatically.

### **SECTION 5. Fire – Fighting Measures**

#### **5.1 Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 5.2 Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

#### 5.3 Specific Hazards Arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Product is or contains a sensitizer.

#### **Hazardous Combustion products**

Carbon oxides.

#### 5.4 Explosion Data

Sensitivity to Mechanical Impact :No. Sensitivity to Static Discharge: No.

#### 5.5 Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/IOSH (approved or equivalent) and full protective gear. Move containers from fire area if you can do it without risk.

## **SECTION 6.** Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### **6.2 Environmental Precautions**

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if

Report No.: HZHY20160721SDS01 Page 6 of 15 Pages

safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

#### **6.3 Methods for containment**

Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

#### 6.4 Methods for cleaning up

Pick up and transfer to properly labeled containers.

### **SECTION 7. Handling and Storage**

### 7.1 Precaution for safe handling

In case of rupture, use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

#### **Incompatible products**

Strong acids. Strong oxidizing agent. Strong bases.

### **SECTION 8. Exposure Controls/Personal Protection**

#### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite	TWA: 2 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	respirable fraction all	synthetic	TWA 2.5 mg/m³(resp)
	forms except graphite	TWA: 5 mg/m³ respirable	
	fibers	fractionsynthetic (vacated)	
		TWA: 2.5 mg/m3 respirable	
		dust natural (vacated)	
		TWA: 10 mg/m3 total dust	
		synthetic (vacated)	
		TWA: 5 mg/m3 respirable	
		fraction synthetic	
		TWA: 15 mppcf natural	
Cobalt lithium	TWA:0.02mg/m <sup>3</sup>	-	
manganese nickel oxide			
182442-95-1			
Lithium	TWA:2.5mg/m <sup>3</sup> F	TWA: 2.5mg/m <sup>3</sup> F	-
hexafluorophosphate		TWA:2.5mg/m <sup>3</sup>	
21324-40-3		dust(vacated)	
		TWA: 2.5mg/m <sup>3</sup>	
Copper	TWA: 0.2 mg/m3 fume	TWA: 0.1 mg/m3 fume	IDLH: 100 mg/m3 dust,
7440-50-8	TWA: 1mg/m3 Cu dust and	TWA: 1 mg/m3 dust and	fume and mist
	mist	mist	TWA: 1 mg/m3 dust and

Report No.: HZHY20160721SDS01 Page 7 of 15 Pages

		(vacated) TWA: 0.1 mg/m3	mist
		Cu	TWA: 0.1 mg/m3 fume
		dust, fume, mist	
Aluminum	TWA:1mg/m <sup>3</sup>	TWA: 15mg/m³ total dust	IDLH:10mg/m <sup>3</sup>
7429-90-5		TWA: 5mg/m³ respirable fraction	Total dust
		(vacated)	TWA:5mg/m³ Respirable dust
		TWA:15mg/m³total dust(vacated)	
		TWA:5mg/m³respirable fraction	
		(vacated)TWA:5mg/m <sup>3</sup> Al	
		Aluminum	

ACGIH TLV: American Conference of Governmental Industrial Hygienists-Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration-Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

#### **Other Exposure Guidelines:**

Vacated limits revoked by the court of Appeals decision in AFL-CLO v. OSHA, 965F, 2d 962(11th Cir., 1992) See section 15 for national exposure control parameters.

#### 8.2 Appropriate engineering controls

#### **Engineering Measures:**

Showers, Eyewash stations, Ventilation systems

#### 8.3 Individual protection measures, such as personal protective equipment

**Respiratory protection:** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Eye /face protection:** if splashes are likely to occur: Wear safety glasses with side shields(or goggles). None required for consumer use.

**Skin protection:** Wear protective gloves and protective clothing. Long sleeved clothing. Imperious gloves.

**Hygiene Measure:** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. No information available.

## **SECTION 9. Physical and Chemical Properties**

Physical State: Solid

Color: Blue

**Odor:** Odorless

**Odor Threshold:** No information available

pH: No data available

Report No.: HZHY20160721SDS01 Page 8 of 15 Pages

Melting/freezing point: No data available

Boiling point/boiling range: No data available

Flash Point: No data available

**Evaporation Rate:** No data available

Flammability (Solid, gas): No data available

Flammability Limit in Air:

**Upper flammability limit:** No data available

Lower flammability limit: No data available

Vapor pressure: No data available

Vapor density: No data available

**Specific Gravity:** No data available

Solubility: Insoluble in water

Partition coefficient:n-octanol/water: No data available

**Autoignition temperature:** No data available

**Decomposition temperature:** No data available

**Kinematic viscosity:** No data available

Dynamic viscosity: No data available

## **SECTION 10. Stability and Reactivity**

#### **Reactivity:**

No data available

#### **Chemical stability:**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions:**

None under normal processing.

#### **Hazardous Polymerization:**

Hazardous polymerization dose not occur.

#### **Conditions to avoid:**

Do not subject battery to mechanical shock. Keep away from open flames, high temperature.

#### **Incompatible materials:**

Strong acids, Strong oxidizing agents. Strong bases.

#### **Hazardous decomposition products:**

Carbon oxides

## SECTION 11. Toxicological Information

Report No.: HZHY20160721SDS01 Page 9 of 15 Pages

#### 11.1 Information on likely routes of exposure

#### **Product information:**

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:

#### Inhalation:

Specific test data for the substance or mixture is not available. Corrosive by inhalation(base on components). Inhalation of corrosion fumes/gases may cause coughing, choking, headache, dizziness and weakness for several hour. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure and increased heart rate. Inhaled corrosion substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

#### **Eye Contact:**

Specific test data for the substance or mixture is not available. Cause burns. (based on components). Corrosion to the eyes and may cause severe damage including blindness. Cause serious eye damage. May cause irreversible damage to eyes.

#### **Skin Contact:**

Specific test data for the substance or mixture is not available. Corrosion (based on components). Cause burns. Toxic in contact with skin. May be absorbed through the skin in harmful amounts.

#### **Ingestion:**

Specific test data for the substance or mixture is not available. Cause burns. ( based on components). Ingestion cause burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

#### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	> 10000mg/kg ( Rat )	-	-
7782-42-5			

#### 11.2 Information on toxicological effects

#### **Symptoms:**

Erythema (skin redness). May cause redness and tearing of eyes. Itching. Rashes. Hives. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/or wheezing.

## 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization:** May cause sensitization of susceptible person, May cause sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects: No information available.

Report No.: HZHY20160721SDS01 Page 10 of 15 Pages

**Carcinogenicity:** the table below whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel	A3	Group 2B		X
oxide				
182442-95-1				
Nickel 7440-02-0	A3	Group 2B		X

**ACGIH** (American Conference of Governmental Industrial Hygienists)

A3- Animal Carcinogen

**IARC** (International Agency for research on Cancer)

Group 2B- Possibly Carcinogenic to humans

**NTP** (National Toxicology Program) Reasonably Anticipated- reasonably anticipated to be a human Carcinogenic.

**OSHA** (Occupational safety and Health Administration of the US Department of Labor) X-Present

Reproductive Toxicity: No information available.

**STOT- single exposure:** No information available.

**STOT- repeated exposure:** Cause damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE)

**Chronic Toxicity:** Prolonged exposure may cause chronic effects. Repeated contact may cause allergic reactions in very susceptible persons. Contain a known or suspected carcinogen. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

**Target Organ Effects:** Respiratory system. Eyes. Skin. Gastrointestinal tract(GI). Blood. Central Nervous System(CNS). Kidney. Liver. Lungs. Nasal cavities.

Aspiration Hazard: No information available.

#### 11.4 Numerical measures of toxicity product information

The following values are calculated based on chapter 3.1 of the GHS document.

ATE mix(oral): 2900 mg/kg

## **SECTION 12. Ecological Information**

**Ecotoxicity**: Water hazard class1(Self-assessment): slightly hazardous for water.

	, <del>,</del>	, . , , , , , , , , , , , , , , , , , ,		
Chemical name	Toxicity to Aglae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Cooper 7440-50-8	96h EC50:0.31-0.045mg/l	96h LC50:0.068-0.0156mg/L (pimephales promelas)		48h EC50:=0.03mg
7440-30-6	(pseudokirchneriella subcapitata)	96h LC50:=0.112mg/L(Poecilia		/1

Report No.: HZHY20160721SDS01 Page 11 of 15 Pages

72h	reticulate)	
EC50:0.426-0.0535mg/l (pseudokirchneriella subcapitata)	96h LC50=0.3mg/L(Cyprinus marpio) 96h LC50=0.8mg/L((Cyprinus	
	marpio)  96h LC50=1.25mg/L(Lepomis macrochirus) 96h	
	LC50=0.052mg/L(Oncorhynchu s mykiss) 96h LC50=0.2mg/L(Pimephales promelas) 96h LC50: <	
	0.3mg/L(Pimephales promelas)	

Persistence and Degradability: No information available

**Bioaccumulation:** No information available

Other adverse effects: No information available

## **SECTION 13. Disposal Considerations**

#### 13.1Waste treatment methods

#### **Disposal methods:**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. Should not be released into the environment.

#### **Contaminated Packaging:**

Dispose of in accordance with federal, state and local regulations.

#### **California Hazardous Waste Codes 141**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper 7440-50-8	Toxic
Aluminum 7429-90-5	Ignitable powder
Cobalt lithium manganese nickel oxide	Toxic
182442-95-1	

## **SECTION 14. Transportation Information**

According to Packing Instruction 965-970 of IATA DGR 57<sup>th</sup> Edition for transportation, the special provision 188 of IMDG. The batteries should be securely packed and protected against

Report No.: HZHY20160721SDS01 Page 12 of 15 Pages

short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, Power and fire sources. Under the condition of road transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport:

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "PI965-967 section II of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT: NOT REGULATED** 

**Proper Shipping Name:** NON REGULATED

**Emergency Response Guide** Number: 147

Hazard Class: N/A

**ICAO:** Not regulated

IATA:

1. Proper Shipping Name: Lithium ion batteries packed with equipment

Hazard Class: N/A

UN Number: Not restricted

Packaging requirement: According to IATA DGR 57th Edition (Effective 1 January-31December 2016), PACKING INSTRUCTION 966 of section II for transportation.

2. Proper Shipping Name: Lithium ion batteries

UN Number: UN3480

Hazard Class: 9

Packaging requirement: According to IATA DGR 57th Edition (Effective 1 January-31December 2016), PACKING INSTRUCTION 965 of section IB for transportation.

**IMDG/IMO:** Not regulated

**Proper Shipping Name:** NON REGULATED

Hazard Class: N/A

**Ems** No.: F-A,S-1

**RID:** Not regulated

**ADR:** Not regulated

**AND:** Not regulated

## **SECTION 15. Regulatory information**

Report No.: HZHY20160721SDS01 Page 13 of 15 Pages

#### **15.1 International Inventories**

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA – United State Toxic Substance Control Act Section 8(b) Inventory

DSL/NDSL – Canadian Domestic Substance List/Non-Domestic Substance List

#### 15.2 US Federal Regulations

SARA 313: Section 313 of Title III of the superfund Amendments and Reauthorization Act of 1986(SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

			<u> </u>
Chemical Name	CAS No.	Weight (%)	SARA313-Threshold values(%)
Cobalt lithium	182442-95-1	44.29	0.1
manganese nickel			
oxide			
Copper	7440-50-8	7.3	1.0
Aluminum	7429-90-5	12	1.0

#### 15.3 SARA 311/312Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### 15.4 CWA (Clean Water Act)

This product contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

		<b>,</b>		
Chemical Name	CWA -	CWA - Toxic	CWA - Priority	CWA -
	Reportable	Pollutants	Pollutants	Hazardous
	Quantities			Substances
Copper 7440-50-8		X	X	
Cobalt lithium		V	V	
manganese nickel		X	X	
oxide182442-95-1				

#### 15.5CERCLA

This material, as supplied, contain one or more substances regulate as a hazardous under the comprehensive Environmental Response Compensation and Liability Act(CERCLA) (40 CFR 302)

Chemic	al Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8		5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

#### 15.6 US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Report No.: HZHY20160721SDS01 Page 14 of 15 Pages

Chemical Name	California Proposition 65
Cobalt lithium manganese nickel oxide 182442-95-1	Carcinogen

U.S State Right-to-Know Regulations

Chemical Name	New	Massachusetts	Pennsylvania	Rhode	IIIinois
	Jersey			Island	
Graphite 7782-42-5	×	×	×		
Cobalt lithium manganese			×	×	×
nickel oxide					
182442-95-1					
Copper 7440-50-8	×	×	×	×	×
Aluminum 7429-90-5	×	×	×	×	
Nickel 7440-02-0	×	×	×	×	×

#### 15.7 International Regulations

#### Canada

WHMIS Hazard Class Non-controlled

### **SECTION 16. Other Information**

#### **According standard:**

GB/T 16483-2008 Safety data sheet for chemical products Content and order of sections ISO 11014:2009(E) Safety data sheet for chemical products – Content and order of sections 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### **Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used material used in combination with any other materials or in any process, unless specified in the test.

#### **Prepared By:**

Guangzhou MCM Certification and Testing Co., Ltd.

1 F No.13, Zhong San Section, ShiGuang Road, Panyu District, Guangzhou City, Guangdong Province, China.

Tel.: 0086-20-34777662 0086-20-34777663 Fax.: 0086-20-34777665-609

WEB: Http://www.mcmtek.com Email: mark.miao@mcmtek.com

**Issuing Date:** July. 25, 2016 **Revision Date:** July. 25, 2016

## Sample Reference Photo

### Model: 16340 3.7V 550mAh



