

Page 1 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer LOS398 (white, grey, black)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MSP MS-Polymer White, Grey, Black

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Seam sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

EURO-LOCK Vertriebs-GmbH, Nordweststr. 3, D-59387 Ascheberg

Phone:+49 (0) 2593 95887-0, Fax:+49 (0) 2593 95887-29 E-Mail: info@euro-lock.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 2593 95887-0 Monday - Thursday 8:00 - 17:00 CET, Friday 8:00 - 13:00 CET

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.



Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

3.2 Mixture

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Acute Tox. 4, H332

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Inaestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Upon contact with stomach acid development of:

Methano

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Skin irritation possible with prolonged contact.

Developement of:

Methanol

The following applies to this substance:

Product results in a poisonous effect.

Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture



Page 3 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

In case of fire the following can develop:

Oxides of carbon Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well ventilated place.

Store in a dry place.

7.3 Specific end use(s)

Professional use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 4 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

The methanol listed below can arise upon contact with water. Chemical Name Methanol Content %: WEL-TWA: 200 ppm (266 mg/m3) (WEL), 200 WEL-STEL: 250 ppm (333 mg/m3 (WEL) ppm (260 mg/m3) (EU) Monitoring procedures: Compur - KITA-119 SA (549 640)

Compur - KITA-119 U (549 657)

Draeger - Alcohol 25/a Methanol (81 01 631)

DFG (D) (Loesungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004)

Draeger - Alcohol 100/a (CH 29 701)

BMGV: ---Other information: Sk (WEL, EU)

Chemical Name	Calcium carbonat	е		Content %:
WEL-TWA: 4 mg/m3 (respirable	e dust), 10 mg/m3	WEL-STEL:		
(total inhalable dust)				
Monitoring procedures:				
BMGV:			Other information:	

©	B Chemical Name	Titanium dioxide			Content %:
\[\frac{1}{2}\]	WEL-TWA: 10 mg/m3 (total inh	alable dust), 4	WEL-STEL:		
	mg/m3 (respirable dust)				
	Monitoring procedures:				
	BMGV:			Other information:	
	Monitoring procedures:		<u></u>	Other information:	

Trimethoxyvinylsilane Area of application	Exposure route /	Effect on health	Doscrinto	Value	Unit	Note
Area or application	Exposure route / Environmental	Effect off fleattfi	Descripto r	value	Onit	Note
	compartment					
	Environment - freshwater		PNEC	0,34	mg/l	
	Environment - marine		PNEC	0,034	mg/l	
	Environment - water,		PNEC	3,4	mg/l	
	sporadic (intermittent) release					
	Environment - sewage		PNEC	110	mg/l	
	treatment plant		11120	'''	g/.	
	Environment - sediment, freshwater		PNEC	0,27	mg/kg	
	Environment - sediment, marine		PNEC	0,12	mg/kg	
	Environment - soil		PNEC	0,046	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	26,9	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,04	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/kg	

М	et	ha	n	ი
	vı	ıщ		v

EURO-LOCK°

Page 5 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005 Replacing version dated / version: 30.11.2016 / 0004 Valid from: 04.07.2017

PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment,		PNEC	570,4	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	57,04	mg/kg	
	marine					
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water,		PNEC	1540	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sewage		PNEC	100	mg/l	
	treatment plant					
	Environment - freshwater		PNEC	20,8	mg/l	
	Environment - marine		PNEC	2,08	mg/l	
	Environment - sediment		PNEC	77	mg/kg	
	Environment - sediment		PNEC	7,7	mg/kg	
Consumer	Human - inhalation	Long term, local	DNEL	50	mg/m3	
Concamo	Traman initiation	effects	DIVEE		ing/inc	
Consumer	Human - dermal	Short term, systemic	DNEL	8	mg/kg	
Consumer	Tidilian deimai	effects	DIVLE	0	body	
		Circoto			weight/day	
Consumer	Human - inhalation	Short term, systemic	DNEL	50	mg/m3	
Consumer	Tidillali - Illilalation	effects	DINLL	30	IIIg/III3	
Consumer	Human - oral	Short term, systemic	DNEL	8	mg/kg	
Consumer	Tiuman - Orai	effects	DINLL	0	body	
		ellects			weight/day	
Consumer	Human - dermal	Long term, systemic	DNEL	8	mg/kg	
Consumer	Tiuman - demiai	effects	DINEL	0	body	
		enecis				
Congumer	Human - inhalation	Long torm avotomic	DNEL	50	weight/day	
Consumer	Human - innaiation	Long term, systemic	DINEL	50	mg/m3	
Canalina	Liver and and	effects	DNEL	8		
Consumer	Human - oral	Long term, systemic	DINEL	0	mg/kg	
		effects			body	
M/	I I was a see all a was all	Object to meet a maile	DNE	40	weight/day	
Workers / employees	Human - dermal	Short term, systemic	DNEL	40	mg/kg	
		effects			body	
			DATE	200	weight/day	
Workers / employees	Human - inhalation	Short term, systemic	DNEL	260	mg/m3	
NA	1, ., .,	effects	DNE	000	/ 2	
Workers / employees	Human - inhalation	Short term, local	DNEL	260	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	40	mg/kg	
		effects			body	
					weight/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	260	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, local	DNEL	260	mg/m3	
		effects				

Titanium dioxide						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	



Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l
	Environment - sewage treatment plant		PNEC	100	mg/l
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw
	Environment - sediment, marine		PNEC	100	mg/kg dw
	Environment - soil		PNEC	100	mg/kg dw
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Safety gloves made of butyl (EN 374)

Protective nitrile gloves (EN 374).

Safety gloves made of fluorocarbon rubber (EN 374).

Safety gloves made of vinyl (EN 374)

Permeation time (penetration time) in minutes:

>480

Minimum layer thickness in mm:

>0,1

Protective hand cream recommended.



(GB)

Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Selection of materials derived from glove manufacturer's indications

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

No

9.1 Information on basic physical and chemical properties

Physical state: Pastelike, Solid

Colour: According to specification Odour: According to Specification Characteristic, Mild

Odour threshold: Not determined pH-value: n.a.

Melting point/freezing point:

Not determined
Initial boiling point and boiling range:

Not determined

Flash point:

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Not determined

Not determined

Not determined

Not determined

Not determined

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Not determined

Not determined

1,4-1,6 g/cm3

Bulk density:

Solubility(ies):

n.a.

Not determined

Water solubility: Insoluble
Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: 400 °C (Ignition temperature)

Decomposition temperature:

Viscosity:

Vi

Viscosity: >20,5 mm2/s (40°C)
Explosive properties: Product is not explosive.

9.2 Other information

Oxidising properties:

Miscibility:

Fat solubility / solvent:

Conductivity:

Surface tension:

Not determined

Not determined

Not determined

Not determined

Solvents content: 0 %

Metal content:

Molar mass:

Not determined

Not determined

Chemical heat of combustion:

Not determined



Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

Protect from humidity.

Product may hydrolyse.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

On contact with moist air:

Methanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

MSP MS-Polymer						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	•					n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						Not irritant, Expert judgement
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute	Aerosol
			' '		Inhalation Toxicity)	

EURO-LOCK°

Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005
Replacing version dated / version: 30.11.2016 / 0004
Valid from: 04.07.2017

PDF print date: 04.06.2019 MSP MS-Polymer (white, grey, black)

Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT- RE):	NOAEC	0,058		Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	
Specific target organ toxicity - repeated exposure (STOT- RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004 Valid from: 04.07.2017

PDF print date: 04.06.2019 MSP MS-Polymer (white, grey, black)

Symptoms:		abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances.
		disturbances, watering eyes,
		nausea, mental confusion

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute	
					Oral toxicity - Fixe	
					Dose Procedure)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
					Irritation/Corrosion)	irritation
						possible.
Respiratory or skin						No (skin
sensitisation:						contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative,
						administered
						as Ca-lactate
Reproductive toxicity:						Negative,
						administered
						as Ca-
						carbonate

Titanium dioxide	For the start	1/-1	1111	0	To at weath and	N-1
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute	
					Oral Toxicity - Up-and-	
					Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
3					Irritation/Corrosion)	irritation
					,	possible.
Respiratory or skin				Mouse	OECD 429 (Skin	Not sensitizising
sensitisation:					Sensitisation - Local	_
					Lymph Node Assay)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
				typhimurium		



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

				OFOD 470 (In Vitar	NI
					Negative
				/	
					Negative
				Mammalian Cell Gene	
				Mutation Test)	
				OECD 471 (Bacterial	Negative
				Reverse Mutation	
				Test)	
			Rat	OECD 414 (Prenatal	No indications
					of such an
				Toxicity Study)	effect.
					Not irritant
					(respiratory
					tract).
					coughing,
					Irritant to
					mucosa of the
					nose and throat
NOAEL	3500	mg/kg/d	Rat		90d
NOAEC	10	mg/m3	Rat		90d
				NOAEL 3500 mg/kg/d Rat	Mutation Test) OECD 471 (Bacterial Reverse Mutation Test) Rat OECD 414 (Prenatal Developmental Toxicity Study) NOAEL 3500 mg/kg/d Rat

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

MSP MS-Polymer								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to algae:							n.d.a.	
12.2. Persistence and							n.d.a.	
degradability:								
12.3. Bioaccumulative							n.d.a.	
potential:								
12.4. Mobility in soil:							n.d.a.	
12.5. Results of PBT							n.d.a.	
and vPvB assessment								
12.6. Other adverse							n.d.a.	
effects:								

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>=100	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATIO N TEST)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>957	mg/l	Scenedesmus subspicatus		88/302/EC



Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004 Valid from: 04.07.2017

PDF print date: 04.06.2019 MSP MS-Polymer (white, grey, black)

12.1. Toxicity to algae:	IC50	72h	>100	mg/l	Selenastrum		
					capricornutum		
12.1. Toxicity to algae:	EC50	72h	>957	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment						,	No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>2500	mg/l	activated sludge		

Methanol										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus					
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna					
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable			
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected			
Other information:	DOC		<70	%						
Other information:	BOD		>60	%						

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209	
						(Activated	
						Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207	Negative
						(Earthworm,	
						Acute Toxicity	
						Tests)	
Water solubility:			0,014	g/l			

Titanium dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203	
_					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	LC50	48h	>100	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchnerie	U.S. EPA-600/9-	
					lla subcapitata	78-018	
12.3. Bioaccumulative	BCF	14d	19-352				Oncorhynchus
potential:							mykiss
12.3. Bioaccumulative	BCF	42d	9,6				No
potential:							
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas		
					fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards:

Not applicable



(B)

Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

n.a.

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %
Directive 2010/75/EU (VOC): 0 g/I

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 8, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds

approx. approximately

EURO-LOCK

LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.07.2017 / 0005 Replacing version dated / version: 30.11.2016 / 0004 Valid from: 04.07.2017 PDF print date: 04.06.2019 MSP MS-Polymer (white, grey, black) Article number Art., Art. no. ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum body weight bw CAS Chemical Abstracts Service CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level **DNEL Derived No Effect Level** DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC **European Community** ECHA European Chemicals Agency European Economic Area EEA **EEC European Economic Community** European Inventory of Existing Commercial Chemical Substances **EINECS ELINCS** European List of Notified Chemical Substances ΕN **European Norms EPA** United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario et cetera etc. EU **European Union** EWC European Waste Catalogue Fax number Fax. gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane **HET-CAM HGWP Halocarbon Global Warming Potential** IARC International Agency for Research on Cancer IATA International Air Transport Association **IBC** Intermediate Bulk Container IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLIDInternational Uniform Chemical Information Database** lethal concentration LC LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical LD



(B)

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2017 / 0005

Replacing version dated / version: 30.11.2016 / 0004

Valid from: 04.07.2017 PDF print date: 04.06.2019

MSP MS-Polymer (white, grey, black)

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.