

Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Trade name: SONAX POWER ICE RUST DISSOLVER

Article number: 04723000

UFI: U9G0-80N1-400A-K59R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Penetrating oil Anticorrosion additive

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

### Further information obtainable from:

Product safety

E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

## SECTION 2: Hazards identification

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

### Signal word Danger

### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

(Contd. on page 2)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

#### 2.3 Other hazards

### Results of PBT and vPvB assessment

### PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

## Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Description: Formulation consisting of pressurised gas and mineral oil with additives in petroleum distillate

Dangerous components:		
EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8  Asp. Tox. 1, H304, EUH066	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ♠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 72623-86-0 EINECS: 276-737-9 Reg.nr.: 01-2119474878-16-XXXX	Lubricating oils (petroleum), C15-30, hydrotreated neutral oilbased  Specific Specif	3-<5%

### Additional information:

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

## 4.1 Description of first aid measures

## General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

### After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 2)

### 4.2 Most important symptoms and effects, both acute and delayed

Reddening, drying and crack formation of the skin

Headache Dizziness

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

## SECTION 5: Firefighting measures

## 5.1 Extinguishing media

## Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Sulphur oxides (SOx)

### 5.3 Advice for firefighters

### Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

### Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation **For non-emergency personnel** Keep away from ignition sources.

For emergency responders Wear protective equipment. Keep unprotected persons away.

## 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

## 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 3)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

## 7.2 Conditions for safe storage, including any incompatibilities

**Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

### Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Ingredients with lin	mit values that require monitoring at the workplace:
Hydrocarbons, C1	1-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics
RCP-TWA (EU)	Long-term value: 1200 mg/m³, 165 ppm Vapour / Total Hydrocarbons
CAS: 106-97-8 buta	ane
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
OEL (Ireland)	Short-term value: 1000 ppm
CAS: 74-98-6 prop	ane
OEL (Ireland)	Asphx
CAS: 75-28-5 isobu	ıtane
OEL (Ireland)	Short-term value: 1000 ppm

## Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs		
CAS: 726	23-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
Inhalative	DNEL	1.2 mg/m³ (consumer) (local / longterm (repeated))
		5.4 mg/m³ (worker) (local / longterm (repeated))

Additional information: The lists valid during the making were used as basis.

### 8.2 Exposure controls

### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

## Individual protection measures, such as personal protective equipment

## General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

### Respiratory protection:

If the occupational exposure limit is exceeded:

(Contd. on page 5)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 4)

The following breathing protection is recommended: Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye/face protection Safety glasses [EN 166]

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:Light yellowOdour:Solvent-likeMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range 180 °C

(Active ingredient data )

**Flammability** Extremely flammable aerosol.

Lower and upper explosion limit

Lower: 0.6 Vol % (Hydrocarbons, C11-C14, n-alkanes,

isoalkanes, cyclics, < 2% aromatics) 10.9 Vol % (CAS: 74-98-6 propane)

Flash point: Not applicable, as aerosol.

**Decomposition temperature:**pH
Not determined.
Not applicable.

Viscosity:

Upper:

Kinematic viscosity at 40 °C <20.5 mm<sup>2</sup>/s

(Active ingredient data)

Solubility

water: Not miscible or difficult to mix.

**Partition coefficient n-octanol/water (log value)**Not determined.
Not determined.

Density and/or relative density

**Density at 20 °C:** 0.8-0.81 g/cm<sup>3</sup>

(Active ingredient data)

Vapour density Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

**Ignition temperature:** Not determined.

**Explosive properties:** In use, may form flammable/explosive vapour-air

mixture.

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void

Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

(Contd. on page 6)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

		(Contd. of page
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values rel	evant for classification:
Hydrocari	bons, C11	I-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5,000 mg/m³ (rat) (OECD 403)
CAS: 726	23-86-0 L	ubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4d	>5,000 mg/l (rat)

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 6)

### 11.2 Information on other hazards Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

## **SECTION 12: Ecological information**

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxic	city:
Hydrocarbor	ns, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)
CAS: 106-97-	8 butane
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
CAS: 74-98-6	propane
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)
CAS: 75-28-5	isobutane
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
CAS: 72623-	86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
NOEC / 2 d	≥10,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 96h	>100 mg/l (fish)
EC50 / 48h	>10,000 mg/l (Daphnia magna) (OECD 202)
ErC 50 / 72h	
NOEC 96h	≥100 mg/l (fish) (OECD 203)
NOEC / 21 d	≥10 mg/l (Daphnia magna) (OECD 211)
	≥100 mg/l (algae)
12.2 Persiste	ence and degradability
Hydroorbor	os C11 C14 n alkanos ispalkanos evolies < 2º/ aromatics

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation 69 % (28d)

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Biodegradation >60 % (28d)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

## 12.5 Results of PBT and vPvB assessment

### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

## vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

### 12.7 Other adverse effects

### Additional ecological information:

General notes: The product may not be released into the environment without control.



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 7)

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10\* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR/RID/ADN	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class	2 5F Gases.
Label	2.1
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	see Sections 6-8
	Warning: Gases.
14.7 Maritime transport in bulk according	to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D



Printing date 20.11.2023 Version: 2.00 (replaces version 1.01) Revision: 19.09.2022

Trade name: SONAX POWER ICE RUST DISSOLVER

(Contd. of page 8)

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 92.41 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

## National regulations:

### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways. H304

EUH066 Repeated exposure may cause skin dryness or cracking.

## Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 On basis of test data

Date of previous version: 22.04.2021 Version number of previous version: 1.01

### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 : Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure - Compressed gas

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.