

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Tar Remover

Article number:

03342000

UFI: 7WC6-T0RD-K00X-J8RY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + 49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

C9-10 Alkane/Cycloalkane

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
 Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Preparation of propellant and solvents**Dangerous components:**

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	25-<50%
EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 110-25-8 EC number: 701-177-3 Reg.nr.: 01-2119488991-20-xxxx	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=1); ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	<0.25%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons

≥30%

(Contd. on page 3)

**Safety data sheet
according to UK REACH**

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover**Additional information:****Hydrocarbon mixture:**

Benzene content < 0.1%

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Drowsiness

Reddening, drying and crack formation of the skin

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

Keep away from ignition sources.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 3)

Do not inhale gases / fumes / aerosols.

Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:


Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

RCP-TWA (EU)	Long-term value: 1200 mg/m ³ , 165 ppm Vapour / Total Hydrocarbons
--------------	--

CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

OEL (Ireland)	Short-term value: 1000 ppm
---------------	----------------------------

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 4)

CAS: 74-98-6 propane

OEL (Ireland) Asphx

CAS: 75-28-5 isobutane

OEL (Ireland) Short-term value: 1000 ppm

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2024 CoP for the Safety, Health and Welfare at Work

DNELs**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	DNEL	46 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
Dermal	DNEL	46 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
		77 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)
Inhalative	DNEL	185 mg/m ³ (consumer) (ChronicExposure, SystemicEffects)
		871 mg/m ³ (worker) (ChronicExposure, SystemicEffects)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Oral	DNEL	92 mg/kg (consumer) (acute systematic effects)
	DNEL	5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	50 mg/kg (consumer) (acute systematic effects)
		10 mg/kg (worker) (longterm systematic effects)
	DNEL	5 mg/kg (consumer) (longterm systematic effects)
		100 mg/kg (worker) (acute systematic effects)
Inhalative	DNEL	9 mg/m ³ (consumer) (acute locale effects)
		18 mg/m ³ (worker) (acute locale effects)
	DNEL	0.005 mg/m ³ (consumer) (longterm local effects)
		0.01 mg/m ³ (worker) (longterm local effects)
	DNEL	0.1 mg/m ³ (consumer) (longterm systematic effects)
		0.2 mg/m ³ (worker) (longterm systematic effects)

PNECs**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

PNEC	0.0043 mg/l (sporadic release)
	0.00043 mg/l (water (fresh water))
	0.000043 mg/l (water (sea water))

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 5)

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

Light brown

Odour:

Solvent-like

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

138-240 °C

Flammability

Extremely flammable aerosol.

Lower and upper explosion limit

Lower:

0.6 Vol % (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

(Active ingredient data)

Upper:

7 Vol % (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

(Active ingredient data)

Flash point:

38 °C (DIN 51755)

(Active ingredient data)

Decomposition temperature:

Not determined.

pH

Not applicable.

Not determined.

Viscosity:

Kinematic viscosity at 40 °C

<20.5 mm²/s (DIN 53211/4)

(Active ingredient data)

Dynamic:

Not determined.

Solubility

water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure:

Not determined.

Density and/or relative density

Density at 20 °C:

0.77-0.78 g/cm³

(Active ingredient data)

Vapour density

Not determined.

9.2 Other information

Appearance:

Form:

Aerosol

Important information on protection of health and environment, and on safety.

Ignition temperature:

Not determined.

Explosive properties:

In use, may form flammable/explosive vapour-air mixture.

Change in condition

Evaporation rate

Not determined.

Information with regard to physical hazard classes

Explosives

Void

Flammable gases

Void

Aerosols

>85% (percent by mass) flammable components, combustion energy ≥ 30 kJ/g
Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Void

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 6)

Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5,000 mg/m ³ (rat) (OECD 403)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC 50 / 8h	>5,000 mg/l (rat) (OECD 403)
	LC50 / 4h	>4,951 mg/m ³ (rat) (OECD 403)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Oral	LD50	5,000 mg/kg (rat) (OECD 401)
		>5,000 mg/kg (rat) (OECD 420)
Inhalative	LC50 / 4h	1.37 mg/m ³ (rat)
		1.8 mg/m ³ (rat) (OECD 403)

Skin corrosion/irritation

Long-term exposure causes slight irritation of the skin.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

May cause slight, short-term eye complaints.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 7)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LC50 / 2 d	>1,000 mg/l (Daphnia magna)
NOEC / 3 d	1,000 mg/l (algae)
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss)
LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)
EC50 / 3 d	>1,000 mg/l (algae)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

LL50 / 96h	>10-<30 mg/l (Oncorhynchus mykiss)
EL50 / 48h	>22-<46 mg/l (Daphnia magna)
EL50 / 72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR 72 h	<1 mg/l (Pseudokirchneriella subcapitata)

CAS: 106-97-8 butane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

CAS: 74-98-6 propane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

CAS: 75-28-5 isobutane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

LC50 / 96 h	6.8 mg/l (fish)
EC20 / 0.5 h	50 mg/l (activated sludge)
EC50 / 48h	0.43 mg/l (Daphnia magna)
EC50 / 72h	6.3 mg/l (Scenedesmus subspicatus)
	0.91 mg/l (Desmodesmus subspicatus) (OECD 201)

12.2 Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	69 % (28d)
----------------	------------

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation	89 % (28d)
----------------	------------

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 8)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

CSB 2,400 mg/g

Biodegradation 85 % (OECD 301 B Ready Biodegradability -. CO2 Evolution)

12.3 Bioaccumulative potential**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

log POW 3.5-4.2

12.4 Mobility in soil

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment**PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:** The product may not be released into the environment without control.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN number or ID number**

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN

**Class**

2 5F Gases.

(Contd. on page 10)

GB

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 9)

Label 2.1

IMDG, IATA


Class 2.1 Gases.
Label 2.1

14.4 Packing group
ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:
Marine pollutant: No

14.6 Special precautions for user see Sections 6-8
Warning: Gases.

Stowage Code SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A.
For AEROSOLS with a capacity above 1 litre: Category B. For WASTE
AEROSOLS: Category C, Clear of living quarters.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for
division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

Transport/Additional information:

ADR/RID/ADN
Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

European Directives:

Directive 2010/75/EU (VOC) 98.64 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing
under Article 5(3))

None of the ingredients is listed.

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

(Contd. of page 10)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1

On basis of test data

Specific target organ toxicity (single exposure)
Hazardous to the aquatic environment - long-term
(chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Date of previous version: 17.12.2024

Version number of previous version: 10.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 12)

**Safety data sheet
according to UK REACH**

Printing date 07.07.2025

Version: 10.01 (replaces version 10.00)

Revision: 16.01.2025

Trade name: SONAX Tar Remover

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
*** Data compared to the previous version altered.**

(Contd. of page 11)

GB