



| | | | | |
|--------|---------|---------|---------|---------|
| PRI ND | 8900022 | 8900023 | 8900024 | 8900025 |
| DN | 1/2 | 3/4 | 1 | 1 1/4 |
| φ | 14.5 | 19 | 24 | 30 |
| L1 | 12 | 13 | 14 | 17 |
| L2 | 12.5 | 13 | 14 | 17 |
| L | 51 | 58 | 66 | 79.5 |
| H | 41 | 43.5 | 50.5 | 53.5 |
| M | 60 | 60 | 70 | 70 |
| PN | 20 | | | |

| NO. | Part name | Material |
|-----|---------------|----------|
| 1 | Body | CW617N |
| 2 | Bonnet | CW617N |
| 3 | Ball | CW617N |
| 4 | PTFE seat | PTFE |
| 5 | Stem | CW617N |
| 6 | Packing gland | PTFE |
| 7 | Packing nut | CW617N |
| 8 | Handle | Aluminum |
| 9 | Hex screw cap | Steel |

Technical requirements:

- 1) Surface: Nickel plated
- 2) Working Temperature: -10°C ~ 80°C
- 3) Max pressure: DN15(1/2")-DN25(1") max. 20bar, DN32(1 1/4") max. 16bar,
- 4) Threaded ends: ISO 228



GmbH

Code

JL-7505

Description