

Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: Rostlöser
Article number: LOS120

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Lubricant

 \cdot 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Euro-Lock Vertriebs-GmbH

Nordweststr. 3

D - 59387 Ascheberg

Tel.: +49 (0) 2593/95887-0 Fax: +49 (0) 2593/95887-29

www.euro-lock.de info@euro-lock.de

· Further information obtainable from:

Tel.: +49 (0) 2593/95887-0 E-Mail: info@euro-lock.de

• **1.4 Emergency telephone number:** Tel.: +49 (0) 2593/95887-0

Monday - Thursday 8.00 a.m. - 5.00 p.m. and Friday 8.00 a.m. - 1.00 p.m.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to hazardous or special waste collection point.

(Contd. on page 2)



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 1)

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304	25-<50%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 64742-53-6 EINECS: 265-156-6 Reg.nr.: 01-2119480375-34-xxxx	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<5%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<2.5%
· Regulation (EC) No 648/2004 or	n detergents / Labelling for contents	

· Regulation (EC) No 648/2004 on detergents / Labelling for contents		
aliphatic hydrocarbons	≥30%	
aromatic hydrocarbons	<5%	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- \cdot After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Mount respiratory protective device.

Keep away from ignition sources.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingre	· Ingredients with limit values that require monitoring at the workplace:			
CAS:	106-97-8 butane			
WEL	Short-term value: 1810 mg/m³, 750 ppm			
	Long-term value: 1450 mg/m³, 600 ppm			
	Carc (if more than 0.1% of buta-1.3-diene)			
CAS:	111-76-2 2-butoxyethanol			
WEL	WEL Short-term value: 246 mg/m ³ , 50 ppm			
	Long-term value: 123 mg/m³, 25 ppm			
	Sk, BMGV			
· Ingre	· Ingredients with biological limit values:			
CAS:	CAS: 111-76-2 2-butoxyethanol			
BMG	BMGV 240 mmol/mol creatinine			

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Filter AX
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

(EN 374)

Recommended thickness of the material: ≥ 0.45 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

≥240 min

· Eye protection:



Tightly sealed goggles

(EN 166)

Body protection:

Protective work clothing

(Contd. on page 5)



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 4) (EN 13034-6)

Not determined.

Not applicable.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic	physical and	chemical	properties
----------------------------	--------------	----------	------------

· General Information

· Appearance:

· pH-value:

Form: Aerosol
Colour: Colourless
• Odour: Petroleum-like
• Odour threshold: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: <0 °C

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: >200 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Not determined.

• Explosive properties: Not determined.

· Explosion limits:

· Evaporation rate

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

Density at 20 °C: 0.69181 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.
Organic solvents: 85,6 %
VOC (EC) 591.9 g/l

Solids content: 0,0 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/L0	· LD/LC50 values relevant for classification:		
ATE (ATE (Acute Toxicity Estimates)		
Oral	LD50	77,321 mg/kg (rat)	
Derma	1 LD50	20,898 mg/kg (rab)	
Inhalat	tive LC50/4 h	575 mg/l	

CAS: 111	CAS: 111-76-2 2-butoxyethanol		
Oral	LD50	500 mg/kg (ATE)	
Dermal	LD50	1,100 mg/kg (ATE)	
Inhalative	LC50/4 h	11 mg/l (ATE)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- $\cdot \ CMR \ effects \ (carcinogenity, mutagenicity \ and \ toxicity \ for \ reproduction)$
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
 - May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

GB ·



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 6)

SECTION 13: Disposal considerations

- \cdot 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

CECTION 14. Tuescon out informed	At on
SECTION 14: Transport informa	tion
14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
	AEROSOLS, Hallillaute
• 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	2 5F Gases.
Label	2.1
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards:	N.
· Marine pollutant:	No
• 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler): · EMS Number:	- F-D.S-U
· Stowage Code	SW1 Protected from sources of heat.
Stowage Code	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated fro class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriate



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

	(Contd. of page
	subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

- · Department issuing SDS: Product Safety department.
- · Contact: Tel.: +49 (0) 2593/95887-0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)



Printing date 09.05.2018 Version number 78 Revision: 09.05.2018

Trade name: Rostlöser Artikel-Nr. LOS120

(Contd. of page 8)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

- GB