Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2020

*

*

Version number 32

Revision: 05.02.2020

SECTION 1: Identifica	tion of the substance/mixture and of the company/undertaking
• 1.1 Product identifier	
· Trade name: <u>Anti-Seize-Cer</u>	amic
 Article number: LOS470 1.2 Relevant identified uses No further relevant informatio Application of the substance 	
 1.3 Details of the supplier of Manufacturer/Supplier: EURO-LOCK Vertriebs-Gmb Nordweststr. 3 D-59387 Ascheberg Tel.: +49 (0) 2593 95887-0 Fax.: +49 (0) 2593 95887-29 www.euro-lock.de Further information obtaina Tel.: +49 (0) 2593 95887-0 E-Mail: info@euro-lock.de 1.4 Emergency telephone nu 	able from:
SECTION 2: Hazards i	
• 2.1 Classification of the subs • Classification according to I	stance or mixture Regulation (EC) No 1272/2008
GHS02 flame	
Aerosol 1 H222-H22	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
GHS05 corrosion	
Eye Dam. 1 H318	Causes serious eye damage.
GHS07	
Skin Irrit. 2 H315	Causes skin irritation.
Asp. Tox. 1 H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3 H412	Harmful to aquatic life with long lasting effects.
 2.2 Label elements Labelling according to Regu The product is classified and b Hazard pictograms 	alation (EC) No 1272/2008 labelled according to the CLP regulation.
GHS02 GHS05	
· Signal word Danger	
Hazard-determining compo- calcium dihydroxide	nents of labelling:
	(Contd. on page 2) GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2020

Version number 32

Revision: 05.02.2020

Trade name: Anti Seize Ceramic

	(Contd. of page 1)	
Distillates (petroleum), hydrotreated heavy paraffini	ic	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloa	llkanes, < 5 % n-hexane	
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalka	nes	
Hazard statements		
H222-H229 Extremely flammable aerosol. Pressuris	sed container: May burst if heated.	
H315 Causes skin irritation.		
H318 Causes serious eye damage.		
H412 Harmful to aquatic life with long lasting	g effects.	
Precautionary statements		
P101 If medical advice is needed, have	e product container or label at hand.	
P102 Keep out of reach of children.		
P210 Keep away from heat, hot surface smoking.	es, sparks, open flames and other ignition sources. No	
P211 Do not spray on an open flame o	r other ignition source.	
P251 Do not pierce or burn, even after	use.	
P261 Avoid breathing vapours or spray	у.	
P271 Use only outdoors or in a well-ventilated area.		
P280 Wear protective gloves / eye pro	tection / face protection.	
P305+P351+P338 IF IN EYES: Rinse cautiously was present and easy to do. Continue	ith water for several minutes. Remove contact lenses, if rinsing.	
P310 Immediately call a POISON CENTER/doctor.		
P410+P412 Protect from sunlight. Do not exp	•	
P501 Dispose of contents/container to	hazardous or special waste collection point.	
Additional information:		
Buildup of explosive mixtures possible without suff	icient ventilation.	
2.3 Other hazards		
Results of PBT and vPvB assessment		

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

 Dangerous components: 		
CAS: 1305-62-0 EINECS: 215-137-3	calcium dihydroxide	20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	 butane, pure Flam. Gas 1, H220; Press. Gas (Comp.), H280 	10-<20%
CAS: 64742-54-7 EINECS: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	10-<20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane ♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225; S Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
	(Con	td. on page 3

[·] Description: Mixture of substances listed below with nonhazardous additions.

Version number 32

Revision: 05.02.2020

(Contd. of page 2)

Trade name: Anti Seize Ceramic

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

- Take affected persons into fresh air and keep quiet.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- Breathing difficulty
- Headache
- Dizziness
- Dizziness
- Coughing
- Nausea
- · 4.3 Indication of any immediate medical attention and special treatment needed
- If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- \cdot Suitable extinguishing agents:
- Fire-extinguishing powder
- Carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

- Foam
- · 5.2 Special hazards arising from the substance or mixture
- Can form explosive gas-air mixtures.
- Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation Keep away from ignition sources.
• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

(Contd. on page 4)



Printing date 05.02.2020

•

⁻ GI

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2020

Version number 32

(Contd. of page 3)

Trade name: Anti Seize Ceramic

Dispose contaminated material as waste according to item 13	3.
Ensure adequate ventilation.	

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 7 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.

• **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) Professional use

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

CAS: 1305-62-0 calcium dihydroxide

WEL Short-term value: 4* mg/m³ Long-term value: 5 1* mg/m³ *resprable fraction

CAS: 106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2020

Version number 32

Trade name: Anti Seize Ceramic

(Contd. of page 4)
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
· Material of gloves

Nitrile rubber, NBR

- Recommended thickness of the material: ≥ 0.45 mm
- · Penetration time of glove material
- \geq 240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:
- Safety glasses

×

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and c	chemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	White
· Odour:	Petrol-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: < 0 °C
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Not determined.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.77623 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
	(Contd. on page 6

GB

Version number 32

Revision: 05.02.2020

Trade name: Anti Seize Ceramic

		(Contd. of page 5
Kinematic:	Not determined.	
Organic solvents:	57.9 %	
VOC (EC)	449.3 g/l	
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Aldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >81.2 mg/l (rat)

CAS: 1305-62-0 calcium dihydroxide

Oral LD50 7,340 mg/kg (rat)

CAS: 74-98-6 propane

Inhalative LC50/4 h >20 mg/l (rat)

CAS: 106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

CAS: 75-28-5 isobutane

Inhalative LC50/4 h 658 mg/l (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

Oral	LD50	>5,000 mg/kg (rat) (OECD Prüfrichtlinie 401)
-		

>2,000 mg/kg (rat) (OECD Prüfrichtlinie 402) Dermal LD50

Inhalative LC50/4 h >20 mg/l (rat) (OECD Prüfrichtlinie 403)

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Oral LD50 >5,840 mg/kg (rat)

Dermal LD50 >2,920 mg/kg (rat) Inhalative |LC50/4 h| > 25.2 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 05.02.2020

Version number 32

Revision: 05.02.2020

Trade name: Anti Seize Ceramic

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

- Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name · ADR/RID/ADN	UN1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
		(Contd. on page 8



Printing date 05.02.2020

(Contd. of page 6)

GB



Printing date 05.02.2020

Version number 32

Trade name: Anti Seize Ceramic

• 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
ADR/RID/ADN	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
2	
· Class	2.1
· Label	2.1
14.4 Packing group	
· ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards:	
· Marine pollutant:	No
• 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
• EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a maximum capacity of T
	1 litre: Category B. For WASTE AEROSOLS: Categor
	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre: Sogragation as for class 9. Stow "songrated from" class
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
• 14.7 Transport in bulk according to Ann Marmal and the IBC Code	
Marpol and the IBC Code	Not applicable.
• Transport/Additional information:	
· ADR/RID/ADN	1L
· Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E0
Zacepteu quantities (DQ)	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L Calto F0
• Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	(Contd. on pa

Printing date 05.02.2020

Version number 32

Revision: 05.02.2020

Trade name: Anti Seize Ceramic

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $150\,t$
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- \cdot 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product Safety department.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • * Data compared to the previous version altered.



(Contd. of page 8)