

according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

LOS 340/2 Revision date: 20.09.2017 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOS 340/2 5-Minute Epoxy (HARDENER)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

professional use. Private households (= general public). Keep out of the reach of children.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

EURO-LOCK Company name: Street: Nordweststrasse 3 Place: D-59387 Ascheberg Telephone:

+49 (0) 2593 - 95 88 7 - 0 Telefax:+ 49 (0) 02593 - 95 88 7 - 29 e-mail: info@euro-lock.de Internet: www.euro-lock.de

Tel.: +49 (0) 2593 - 95 88 7 - 0 Responsible Department:

Monday - Thursday 08.00 am - 17.00 pm, Friday 08.00 am - 13.00 pm

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1C

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eve damage. May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Polymercaptane

2,4,6-tris(dimethylaminomethyl)phenol bis[(dimethylamino)methyl]phenol

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 2 of 13

Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container to local/regional/national/international regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regula	tion (EC) No. 1272/2008 [CLP]			
72244-98-5	Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether				
	615-735-8		01-2120118957-46		
	Skin Sens. 1B, Aquatic Chronic 3;	H317 H412			
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol			5 - < 10 %	
	202-013-9		01-2119560597-27		
	Skin Corr. 1C, Eye Dam. 1, Skin S	Sens. 1B; H314 H318 H317			
71074-89-0	bis[(dimethylamino)methyl]phenol			1 - < 5 %	
	275-162-0				
	Skin Corr. 1C; H314				

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks).



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 3 of 13

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx) Gas/vapours, toxic.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8).

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 4 of 13

Conditions to avoid: aerosol or mist formation Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

Advices on general occupational hygiene: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 20°C

Protect against: Light. UV-radiation/sunlight. heat. moisture.

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
72244-98-5	Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, etl 2-hydroxy-3-mercaptopropyl ether	ner with 2,2-bis(hydrox	xymethyl)-1,3-propane	ediol (4:1),
Worker , long	-term	inhalation	systemic	22 mg/m ³
Worker , long-term		dermal	systemic	2,7 mg/kg bw/day
Consumer , long-term		inhalation	systemic	6,52 mg/m ³
Consumer , long-term		dermal	systemic	1,61 mg/kg bw/day
Consumer , long-term		oral	systemic	1,9 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment Value		Value	
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether			
Freshwater		0,07 mg/l	
Marine water		0,007 mg/l	
Freshwater s	ediment	0,322 mg/kg	
Marine sediment 0,0		0,032 mg/kg	
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l	
Soil 0,023 mg.		0,023 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 5 of 13







Appropriate engineering controls

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink or smoke. Wash hands before breaks and after work. Remove contaminated clothing immediatley and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored seperately from work clothing.

Eye/face protection

Wear eye/face protection. DIN EN 166

Hand protection

Wear suitable gloves.

Suitable material:

PVC (Polyvinyl chloride). - Thickness of glove material: 0,5 mm

Breakthrough time >= 8 h

Rubber. - Thickness of glove material: 0,5 mm

Breakthrough time >= 8 h

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

- -exceeding exposure limit values
- -insufficient ventilation and aerosol or mist formation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type A-P2

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellowish
Odour: rotten eggs.

Test method

pH-Value: 3



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 6 of 13

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No information available.

Flash point:

>200 °C

Sustaining combustion:

No data available

Flammability

Solid: No information available.

Gas: No information available.

Explosive properties

not explosive.

Lower explosion limits:

Upper explosion limits:

No information available.

No information available.

No information available.

Auto-ignition temperature

Solid:
Gas:
No information available.
No information available.

Decomposition temperature:
No information available.

Oxidizing properties

none

Vapour pressure: No information available.

(at 20 °C)

Vapour pressure: No information available.

(at 50 °C)

Density (at 20 °C): 1,15 g/cm³ ISO 2811

Bulk density:

Water solubility:

No information available.

No information available.

Solubility in other solvents

No information available.

Partition coefficient: No information available. Ca. 10000 mPas Viscosity / dynamic: No information available. Viscosity / kinematic: Flow time: No information available. No information available. Vapour density: Evaporation rate: No information available. Solvent separation test: No information available. Solvent content: No information available.

9.2. Other information

Solid content: No information available.

SECTION 10: Stability and reactivity



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 7 of 13

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx) Gas/vapours, toxic.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
72244-98-5		Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether				
	oral	LD50 26 mg/kg	600	Rat.	ECHA Dossier	
	dermal	LD50 >	10200	Rabbit	ECHA Dossier	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol					
	oral	LD50 [2 mg/kg	21699	Rat	ECHA Dossier	
	dermal	LD50 [> mg/kg	>971]	Rabbit	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether;

2,4,6-tris(dimethylaminomethyl)phenol)

Carcinogenic/mutagenic/toxic effects for reproduction



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 8 of 13

Based on available data, the classification criteria are not met.

 $Poly[oxy(methyl-1,2-ethanediyl)],\ a-hydro-?-hydroxy-,\ ether\ with\ 2,2-bis(hydroxymethyl)-1,3-propanediol\ (4:1),$

2-hydroxy-3-mercaptopropyl ether:

In vitro mutagenicity/genotoxicity: Method: OECD 471 (Ames test).; Result / evaluation: negative.

2.4.6-tris(dimethylaminomethyl)phenol:

In vitro mutagenicity/genotoxicity: Method: OECD 471 (Ames test).; Result / evaluation: negative.; Reproductive toxicity: Method: OECD 422.; Species: Rat.; Exposure duration: 54 d.; Result: NOAEL 15 mg/kg bw/day.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether:

Subchronic oral toxicity: Method: OECD 408; Species: Rat.; Exposure duration: 90 d.; Result: NOAEL 75 mg/kg bw/day.

2,4,6-tris(dimethylaminomethyl)phenol:

Subchronic oral toxicity: Method: OECD 422. ; Species: Rat. ; Exposure duration: 54 d.; Result: NOAEL 15 mg/kg bw/day.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
72244-98-5	Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether					diol (4:1),	
	Acute fish toxicity	LC50	87 mg/l	96 h	Brachydanio rerio (zebra-fish)	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	>733		Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50	12 mg/l	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC	3,5 mg/l	21 d	Daphnia magna	ECHA Dossier	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol						
	Acute algae toxicity	ErC50	(84) mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	

12.2. Persistence and degradability

The product has not been tested.



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 9 of 13

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	-			
72244-98-5	Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether				
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	5%	28	ECHA Dossier	
	Not readily biodegradable (according to OECD criteria)				
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol				
	OECD 301D/ EEC 92/69/V, C.4-E	4%	28	ECHA Dossier	
	Not readily biodegradable (according to OECD criteria)				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72244-98-5	Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-?-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	>1,2
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	>=0,219

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 10 of 13

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

 $(2,\!4,\!6\text{-tris}(dimethylaminomethyl)phenol)$

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C7
Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-tris(dimethylaminomethyl)phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C7
Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-tris(dimethylaminomethyl)phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

EmS:

NO

223, 274

5 L

E1

F-A, S-B



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 11 of 13

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(2,4,6-tris(dimethylaminomethyl)phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A803

1 L

Y841

Excepted quantity:

E1

IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work

protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Changes

Rev.: 3.0 - 20.09.2017 Initial release



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 12 of 13

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Roglement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

	9
Classification	Classification procedure
Skin Corr. 1C; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1B; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Causes serious eye damage.

Harmful to aquatic life with long lasting effects.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of



according to Regulation (EC) No 1907/2006

5-Minute Epoxy (HARDENER)

Revision date: 20.09.2017 LOS 340/2 Page 13 of 13

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)