TECHNICAL DATA SHEET



Protection Wax

Protection Wax is an ideal protection from rust in grooves and on surfaces! It offers long-lasting protection from corrosion, oxidation and dirt. After the wax has dried up, there remains a sticky, plasticine-like, water-repellent film which is almost colourless. Saltwater and heat-resistant (100°C). Its excellent flow properties make Protection Wax also suitable for inaccessible areas. Protection Wax is used for preserving grooves, surfaces and cavities in motor vehicles, building machinery, agricultural implements as well as for gadgets employed in household and garden. Its light colour makes it particularly suitable for the protection of grooves in car bonnets and boots.

Protection Wax is suitable for both a secondary treatment, such as after an accident, and a first treatment.

It is also a preferred means of preserving an engine compartment that has just been cleaned.

Use:

Before use, pre-treat Protection Wax, if necessary, with a cleaner, primer or Zinc-Aluminium Spray. Spray the wax on in a thin layer and let it dry. Plastic and rubber are not affected.

Content of aerosol can:

400 ml

Suggestions, processing and use of our products correspond to the best knowledge at printing of this leaflet and are always given without obligation. You only can serve as a clue in consideration of the changing conditions; from this no liabilities, liability and guarantee claims can be derived. Own tests must be carried out before application. Every manufacturer of our products is liable for the retention everything legal to regulations.