

Printing date 06.06,2018 Version number 302 Revision: 24.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: LOS170 Silikon-Spray

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

EURO-LOCK Vertriebs-GmbH Nordweststraß 3

D-59387 Ascheberg

Tel.:+49(0)2593 95887-0 *Fax*: +49(0)2593 95887-29

www.euro-lock.de

E-Mail: info@euro-lock.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

+49(0)2593 95887-0 Monday - Thursday 8:00 - 17:00 CET, Friday 8:00 - 13:00 CET

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

(Contd. on page 2)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane	Flam. Gas 1, H220; Press. Gas C, H280	10-<25%	
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane	Flam. Gas 1, H220; Press. Gas C, H280	10-<25%	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane	(b) Flam. Gas 1, H220; Press. Gas C, H280	10-<25%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

(Contd. of page 2)

- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) Industrial processing

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:



Protective gloves

Protective gloves and protective skin cream

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance: Form:

Aerosol Colour: Colourless · Odour: Characteristic · Odour threshold: Not determined.

Not determined. · pH-value:

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

Not applicable, as aerosol. · Flash point:

· Flammability (solid, gas): Not applicable.

(Contd. on page 5)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

	(Contd. of pa
· Ignition temperature:	260 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.9 Vol %
· Oxidising properties	Not determined.
· Vapour pressure at 20 °C:	4200 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	88.7 %
VOC (EC) %	560.0 g/l
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

 CAS: 106-97-8 butane

 Inhalative | LC50/4h | 658 ppm (rat)
 - · Primary irritant effect:
 - · Skin corrosion/irritation Based on available data, the classification criteria are not met.
 - · Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

(Contd. of page 5)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

· European waste catalogue			
16 05 04*	gases in pressure containers (including halons) containing hazardous substances		
15 01 10*	packaging containing residues of or contaminated by hazardous substances		

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1950

(Contd. on page 7)



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

	(Contd. of page
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS (Naphtha (petroleum), hydrotreated ligh (Benzene < 0.1%)), MARINE POLLUTANT
· IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
Label	2.1
IMDG, IATA	
· Class	2.1
Label	2.1
14.4 Packing group	
· ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substance Naphtha (petroleum), hydrotreated light (Benzene < 0.1%
Marine pollutant:	Yes
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
14.7 Transport in bulk according to Annex	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Transport category	3
Tunnel restriction code	E
UN "Model Regulation":	UN1950, AEROSOLS, ENVIRONMENTALL HAZARDOUS, 2.1

SECTION 15: Regulatory information

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 06.06.2018 Version number 302 Revision: 24.05.2018

Trade name: Silikon-Spray

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

- · Department issuing SDS: Product safety department
- · Contact: Head of Product Safety Department

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

 ${\it IATA: International Air Transport Association}$

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

 $Aerosol \ 1: Aerosols - Category \ 1$

Press. Gas C: Gases under pressure - Compressed gas

_ CE